

# Datavideo Product Compare

<https://www.datavideo.com/ap/>

|                        |                                                                                                                  |
|------------------------|------------------------------------------------------------------------------------------------------------------|
| Model Number           | <b>ITC-100</b>                                                                                                   |
| Product                | <b>Intercom System</b>                                                                                           |
| Tally                  | 2 x 15 Pin DSub Sockets for Tally A and B                                                                        |
| MIC / Headset          | 3.5 mm Stereo Jack Socket for Headphone / Microphone combination<br>Headset Impedance 8-600 Ohms 100 mW (min)    |
| Headphone              | ¼" (6.3mm) Stereo Headphone Socket<br>Headset Impedance 8-600 Ohms 100 mW (min)                                  |
| Light Socket (DC 12 V) | 3 PIN XLR Connector<br>PIN 2: 12V<br>PIN 3: GND<br>Light Power Consumption: 12 V / 100 mA (MAX.)                 |
| Microphone             | 3 PIN XLR / ¼" (6.3mm) Jack Microphone Socket<br>Switchable Condenser / Dynamic Input<br>Microphone Level -67 dB |
| Frequency Response     | 550-3.6 kHz, <+/- 3dB                                                                                            |
| THD                    | < 3%                                                                                                             |
| S/N                    | > 50dB                                                                                                           |
| Built-in Speaker       | 70mm x 30mm 32 Ohm 3 Watts                                                                                       |
| Operating Range        | Up to 200 meters between base station and slave                                                                  |
| Operating Temp. Range  | 0~40 °C                                                                                                          |

|                   |                                                                                                                                                                                                                                                                                                       |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Dimension (LxWxH) | 482 x 127 x 46 mm                                                                                                                                                                                                                                                                                     |
| Weight            | 1.9 kg                                                                                                                                                                                                                                                                                                |
| Power             | DC 12V, 8W                                                                                                                                                                                                                                                                                            |
| What's in the Box | 1 x ITC-100 Base Unit<br>4 x ITC-100SL Belt Pack<br>4 x ITC-100SL Carry Case<br>4 x Cable 5piin XLR to XLR<br>4 x 3.5mm Jack to 3.5mm Jack Cable<br>4 x Headset with microphone<br>4 x Tally LED Indicator<br>1 x XLR Gooseneck Microphone<br>1 x XLR Gooseneck Light<br>1 x 12V 1A Power Supply Unit |