

Bundles

## 4 Channel HD Portable Video Production Studio

### GO 650 Studio

Video Standard	HD
Video Format	1080i 50/59.94/60Hz 720p 50/59.94/60Hz
Video Processing	SDI: 4:2:2 HDMI: YUV 4:2:2 10 bit, RGB: 4:4:4
Video Input	2x HD-SDI 2x HDMI
Video Output	1x HDMI
Audio Input	1x Stereo RCA (L/R) 2x Mono Microphone De-embedded Digital Audio (2 CH)
Audio Output	1x Stereo RCA (L/R) 1x Stereo headphone (Mini Jack with volume control) Embedded Digital Audio (2 CH)
Embedded Audio Support	Embedded 2-CH digital/analogue audio
Chroma Key	2
USK	1x USK support Chroma Key & Linear/ Luma Key
DSK	1 (Logo)
Picture in Picture	1
Logo Insertion	1
Still Store	500
Effects	FTB, Cut, 32 Wipe with border
Tally Output	1x D-sub 15pin, dual color
Built-in Audio Mixer	Yes
Preview Display	Dual 10.1" LCD
Special Features	Stinger Effect

### Streaming

Streaming Encode	H.264/AVC, Main/High Profile
Streaming Video Bitrate	Record Only: Up to 16Mbps (1080p50/60) Stream Only: Up to 10Mbps (1080p50/60) Rec+Stream: 10Mbps (1080p25/30)
Streaming Video Rate Mode	CBR
Streaming Audio Mode	Stereo/Mono
Streaming Audio Bitrate	Stereo: 64~384Kbps Mono: 32~192Kbps

Streaming Protocols	TS over TCP/UDP (unicast & multicase) RTSP over HTTP/TCP/UDP (RTSP Elementary Streaming) RTMP/RTMPS (Publish) HLS
Network Interface	1x RJ45 (10/100Mbps Ethernet)
Streaming Recording File Format	H.264
Streaming Storage	SD Card

## Recording

Recording Storage Medium	SD Card
How to Retrieve Recorded Content	Removable Hard Drive, transfer data via USB 2.0
Recording Storage File System	NTFS, FAT
Recorded File Format	MP4

## Audio

Audio Input	----
Audio Output	----
Audio Indicator	----
Audio Delay	----

## Others

Dimension (LxWxH)	493 x 253 x 331 (monitor's up) 493 x 253 x 190 (monitor's down)
Weight	16 kg
Power	DC 12V, 83W
Operating Temp. Range	0~40 °C
What's in the Box	1 x GO 650 Studio Product 1 x AD Switch DC 12V 1 x AC Cord 3 x HDMI Cable 2 x BNC Cable 1 x Ethernet Cable 10 x Cable Ties