

LCD Monitors

2 x 7" HD/SD TFT LCD Monitor

TLM-702HD

Screen	2x7" LED Backlit
Chassis	3RU Rack Mount
Resolution	800x480
Viewing Angle	(H) +70/-70° (V) +50/-70°
Luminance/Contrast	300cd/m ² 500:1
Video Inputs	2x HD/SD-SDI 2x HD/SD-YUV 2x HDMI 2x Composite Video
Loop Through	----
Supported Input Resolutions	1080i(50/60Hz) 720p(50/60Hz) 480i(NTSC) 576i(PAL)
Aspect Ratio	16:9, 15:9, 4:3
Aspect Marker	YES
Safety Marker	YES
Tally LED	Live (Red) Cued (Amber)
Audio In/Out	Embedded Audio on SDI and HDMI Audio Level Indicator, 2x Stereo Headphone Jack
Special Features	Blue Only, Safe Frame, SDI Time Code Display, Audio Level Indicator
Dimension (WxHxD)	485 x 135 x 75mm
Weight	2.2 Kg
Operating Temp. Range	0~40 °C
Power	DC 12V, 18W
What's in the Box	1 x TLM-702HD product 1 x 1.5 ψHex Wrench 1 x 2.5 ψHex Wrench 1 x AD Switch DC 12V