

Repeaters and Distribution

**4K HDMI Distribution Amplifier 1x4****VP-840**

Video Input/Output	Input: 1 x HDMI Output: 4 x HDMI
Video Format	<p>HDMI Supported Resolutions  4096x2160p60/59.94/50  4096x2160p30/29.97/25/24/23.98  3840x2160p60/59.94/50  3840x2160p30/29.97/25/24/23.98  1080p60/59.94/50,  1080p30/29.97/25/24/23.98  1080i60/59.94/50, , 720p60/59.94/50  480p, 576p, 480i, 576i</p> <p>PC Supported Resolutions  640x480@60Hz, 800x600@60Hz, 1024x768@60Hz, 1280x720@60Hz, ,  1280x768@60Hz, 1280x960@60Hz, 1280x1024@60Hz, 1360x768@  60Hz, 1366x768@60Hz, 1400x1050@60Hz, 1680x1200@60Hz,  1920x1080@60Hz, 1920x1200@60Hz</p>
Video Standard	----
Video Processing	HDR 4K2K@60 4:2:0 10bits 4K2K 60Hz YCbCr4:4:4 8bit/YCbCr4:2:0 10bit 4K2K 30Hz YCbCr4:4:4 8bit
Video bandwidth	Single-link 600MHz (18Gbps)
Audio Format	DTS-HD Master Audio, Dolby TrueHD, Dolby Digital, DTS, DVD-Audio, LPCM, SACD, MPCM
Power	12V / 6W
Dimension (LxWxH)	174 x 63 x 35 mm
Weight	0.35 kg
Operating Temp. Range	0~40 °C
What's in the Box	1 x VP-840 product 1 x AD Switch DC 12V