

Caméras

# Caméra Block HD

## BC-80

|                                  |                                                                                                         |
|----------------------------------|---------------------------------------------------------------------------------------------------------|
| Video format/Resolution          | 1080p 59.94/50/29.97/25<br>1080i 59.94/50<br>720p 59.94/50                                              |
| Image Sensor                     | 1/2.8" type progressive scan CMOS sensor                                                                |
| Effective Pixels (approx.)       | 2.14 Mega pixels                                                                                        |
| S/N Ratio                        | 50 dB                                                                                                   |
| Min. Illumination                | Color : 0.4 lx (F1.6, 1/30 sec, 50IRE, Gain: High)<br>B/W : 0.03 lx (F1.6, 1/30 sec, 50IRE, Gain: High) |
| Electronic Shutter               | 1/25~1/1250 sec (50/25Hz)<br>1/30~1/1500 sec (59.94/29.97Hz)                                            |
| Zoom Ratio                       | 30x Optical Zoom                                                                                        |
| Gamma Control                    | Off / Normal / Standard Mode 1-4                                                                        |
| Iris Control                     | Auto / Manual                                                                                           |
| Digital Noise Reductions         | Yes                                                                                                     |
| On-Screen Display (OSD)          | English                                                                                                 |
| White Balance                    | AWB, MWB, One push WB, Outdoor, Indoor, Fluorescent                                                     |
| AGC / Gain Control               | Auto / Manual (0 to 28 step)<br>Max. Gain Limit (6 to 28 step)                                          |
| HDR/WDR                          | WDR                                                                                                     |
| Mirror / Flip Image              | Yes                                                                                                     |
| Focus Mode                       | Auto / Manual                                                                                           |
| Panning / Tilting Range          | ----                                                                                                    |
| Panning / Tilting Speed          | ----                                                                                                    |
| Preset                           | 10 Position                                                                                             |
| Focal Length                     | f=4.3 mm (WIDE) to 129 mm (TELE)<br>F1.6 to F4.7                                                        |
| Field of View (Horizontal, Wide) | Approx. 63.7° (WIDE END) / 2.3° (TELE END)                                                              |
| Image Compensation               | Day & Night function                                                                                    |
| Video Output                     | HDMI (V1.3) x 1<br>3G-SDI x 1                                                                           |
| Audio Input                      | ----                                                                                                    |
| Tally LED                        | Dual color (Red, Green)                                                                                 |
| Lens Filter                      | M52.0 x 0.75 Thread with UV Protection                                                                  |
| Control Protocol                 | VISCA / DVIP Protocol                                                                                   |
| Remote Control Interface         | RS-422: Transmit up to 1000m<br>DVIP (RJ45): 100m                                                       |

|                                    |                                                                          |
|------------------------------------|--------------------------------------------------------------------------|
| Video Compression Format           | ----                                                                     |
| Audio Compression Format           | ----                                                                     |
| Audio Bitrate                      | ----                                                                     |
| HD IP Interface                    | ----                                                                     |
| Streaming Protocols                | ----                                                                     |
| First Stream Supported Resolution  | ----                                                                     |
| Second Stream Supported Resolution | ----                                                                     |
| Video Bitrate                      | ----                                                                     |
| Video Bitrate Mode                 | ----                                                                     |
| Encoding Frame rate                | ----                                                                     |
| POE                                | ----                                                                     |
| F/W Update                         | USB                                                                      |
| IR Control                         | Yes                                                                      |
| Camera Control Unit                | RMC-180 series/RMC-300 series/PTZ View Assist APP                        |
| Tripod Mount                       | 1/4-20 UNC                                                               |
| Optional Accessories               | ----                                                                     |
| Color                              | Dark blue                                                                |
| Dimension (LxWxH)                  | 71 x 202 x 83 mm                                                         |
| Weight                             | 0.7 kg                                                                   |
| Operating Temp. Range              | 0~40 °C                                                                  |
| Power                              | DC 12V 15W                                                               |
| What's in the Box                  | 1 x BC-80 main unit<br>1 x IR remote control<br>1 x DC 12V power adaptor |