

Décodeur vidéo

Décodeur vidéo IP

NVD-20

Audio/Video Input	Stream Input · RTSP over UDP (Unicast / Multicast) · RTSP over TCP · RTSP over HTTP · MPEG-TS over UDP · RTMP over TCP · UDP raw (Unicast/Multicast) · HLS over HTTP
Audio Output	2 x RCA Connectors HDMI embedded audio
Video Output	Composite (analogue) HDMI (digital)
Network Feature	1x RJ-45 Female (10/100M Ethernet) DHCP/Static IP
Supported Video Resolution	480i 60 (NTSC) 576i 50 (PAL) 720p 60/59.94/50 1080i 60/59.94/50 1080p 60/59.94/30/29.97/25/24
Supported Decoding Resolution	Up to 1080p30/25
Control	Web browser UI for configuration and control
Update	Automatic firmware upgrade
Power	Input AC 100~240V Switching Adaptor Output DC 12V / 0.5 A
Environmental Conditions	Operating temperature□0~50°C Storage temperature□-10~60°C
Dimension (LxWxH)	220 x 143 x 47 mm
Weight	1 kg
Power	DC 12V, 0.5A
What's in the Box	1 x NVD-20 product 1 x AD Switch DC 12V 1 x CD for IP Finder