

Décodeur vidéo

# Décodeur vidéo IP

**NVD-25**

|                               |                                                                                                                                                                                                                                                                      |
|-------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Audio/Video Input             | Stream Input <ul style="list-style-type: none"><li>· RTSP over UDP (Unicast / Multicast)</li><li>· RTSP over TCP</li><li>· RTSP over HTTP</li><li>· MPEG-TS over UDP</li><li>· RTMP over TCP</li><li>· UDP raw (Unicast/Multicast)</li><li>· HLS over HTTP</li></ul> |
| Audio Output                  | 2 x RCA Connectors<br>SDI embedded audio                                                                                                                                                                                                                             |
| Video Output                  | Composite (analogue)<br>SDI (digital)                                                                                                                                                                                                                                |
| Network Feature               | 1x RJ-45 Female (10/100M Ethernet) DHCP/Static IP                                                                                                                                                                                                                    |
| Supported Video Resolution    | 480i 60 (NTSC)<br>576i 50 (PAL)<br>720p 60/59.94/50<br>1080i 60/59.94/50<br>1080p 60/59.94/30/29.97/25/24                                                                                                                                                            |
| Supported Decoding Resolution | Up to 1080p30/25                                                                                                                                                                                                                                                     |
| Control                       | Web browser UI for configuration and control                                                                                                                                                                                                                         |
| Update                        | Automatic firmware upgrade                                                                                                                                                                                                                                           |
| Power                         | Input AC 100~240V Switching Adaptor<br>Output DC 12V / 1A                                                                                                                                                                                                            |
| Environmental Conditions      | Operating temperature□0~50°C Storage temperature□-10~60°C                                                                                                                                                                                                            |
| Dimension (LxWxH)             | 220 x 143 x 47 mm                                                                                                                                                                                                                                                    |
| Weight                        | 1 kg                                                                                                                                                                                                                                                                 |
| Power                         | DC 12V, 1A                                                                                                                                                                                                                                                           |
| What's in the Box             | 1 x NVD-25 product<br>1 x AD Switch DC 12V<br>1 x CD for IP Finder                                                                                                                                                                                                   |