

Datavideo Product Compare

<https://www.datavideo.com/fr/>

Numéro de modèle	HS-1200
Product	Studio portable, 6 canaux HD
Video Standard	HD
Video Format	1080i 50/59.94/60Hz 720p 50/59.94/60Hz
Input Routable / Crosspoint	All 6, repeatable
Video Input	4x HD-SDI 2x HDMI
Computer Graphic Interface	2 via HDMI
Down-converted Output	----
Video Output	1x HDMI + 2x SDI assignable: AUX 1-6, PGM, PVW, PGM Clean or multiview
Analogue Audio Input	2x Balanced XLR
Analogue Audio Output	1x Stereo headphone

Digital Embedded Audio Support	2 ch Audio embedded
Audio Delay Calibration	----
A+V Switching	----
USK	2x USK support Chromakey
DSK	2x DSK support Lumakey & Linear key (Key / Fill)
Picture in Picture	1
Logo Insertion	----
Title Creator	----
Built-in Audio Mixer	----
Built-in Monitor Display	17.3" HD TFT LED backlit, 1600x900 pix
Built-in Intercom & Tally	----
Streaming	
Streaming	----
Streaming Audio Encode	----
Streaming Protocol	----
Streaming Control	----

Recording File System	----
Recording File Format	----
Streaming & Recording Setting Control	----
Others	
Special Features	
Dimension (LxWxH)	455 x 355 x 134 mm
Weight	15.4 Lbs (7 kg), Reinforce Plastic Case
Power	DC 12V, 5A
Operating Temp. Range	0~40 °C
What's in the Box	1 x HS-1200 Product 1 x AD Switch DC 12V with AC Cord