

Datavideo Product Compare

<https://www.datavideo.com/fr/>

Numéro de modèle	HS-2800
Product	Studio Mobile HD/SD 8/12 canaux
Video Standard	HD & SD
Video Format	1080i 50/59.94/60Hz 576i 50Hz 480i 59.94Hz
Input Rutable / Crosspoint	Fixed
Video Input	Standard: 8x SDI, 2x HDMI Max: 12x SDI, 3x HDMI
Computer Graphic Interface	Max 3 via HDMI
Down-converted Output	2x SDI
Video Output	2x SDI assignable: PGM, PVW, AUX & Clean Out 1x HDMI assignable: PGM & multi-view
Analogue Audio Input	4x Balanced XLR

Analogue Audio Output	2x Balanced XLR
Digital Embedded Audio Support	Input up to 16 channels, Output 4 channels
Audio Delay Calibration	Up to 8 frames
A+V Switching	Yes
USK	----
DSK	2x DSK support Lumakey & Linear key (Key / Fill)
Picture in Picture	2
Logo Insertion	2 (or 1 logo + 1 clock)
Title Creator	
Built-in Audio Mixer	----
Built-in Monitor Display	
Built-in Intercom & Tally	8 channels (4 belt-packs incl.)
Streaming	
Streaming	----
Streaming Audio Encode	----
Streaming Protocol	----

Streaming Control	----
Recording File System	----
Recording File Format	----
Streaming & Recording Setting Control	----
Others	
Special Features	----
Dimension (LxWxH)	455 x 355 x 134 mm
Weight	18.7 Lbs (8.5 kg), Reinforce Plastic Case
Power	DC 12V, 6A
Operating Temp. Range	0~40 °C
What's in the Box	1 x HS-2800 Unit 1 x AD Switch DC 12V with AC Cord 1 x CB-41 / XLR to XLR Cable 4 x CB-3 / XLR cable 1 x Goose neck MIC 4 x Headphone Microphone 4 x ITC-100SL 1 x Tally light 4 x Velcro