

# Datavideo Product Compare

<https://www.datavideo.com/fr/>

|                                 |  |
|---------------------------------|--|
| Numéro de modèle                | <b>KMU-300</b>   |
| Product                         | <b>Commutateur ROI écran tactile multicanal 4K</b>   |
| Video Standard                  | UHD & HD   |
| Video Format                    | Input:<br>3840x2160p 23.98/24/25/29.97/30/50/59.94/60<br>1080p 50/59.94/60<br>Output:<br>1080p 50/59.94/60<br>720p 50/59.94/60 |
| Video Format                    | 4:4:4 / 4:2:2 / 4:2:0  |
| Video Input                     | 1x HDMI 2.0<br>1x HDMI 1.4 with Loop through   |
| Video Output                    | 3x HDMI 1.4 (Program)<br>1x HDMI 1.4 (Aux: Ch1-Ch4)  |
| Support Video Output Resolution | 1920 x 1080p 50/59.94/60<br>1280 x 720p 50/59.94/60  |
| Multiview Out                   | ---  |
| Multiview Mode                  | ---  |
| <b>Streaming</b>                |  |

|                               |   |
|-------------------------------|---|
| Streaming Encode              | H.264/AVC, Main/High Profile  |
| Streaming Video Bitrate       | Record Only: Up to 16Mbps (1080p50/60)<br>Stream Only: Up to 10Mbps (1080p50/60), dual stream<br>Record+Stream: 36Mbps (1080p50/60) |
| Streaming Video Rate Mode     | CBR   |
| Streaming Audio Mode          | Stereo/Mono   |
| Streaming Audio Bitrate       | Stereo: 64~384Kbps<br>Mono: 32~192Kbps  |
| Streaming Protocols           | TS over TCP/UDP (unicast & multicast)<br>RTSP over HTTP/TCP/UDP (RTSP Elementary Streaming)<br>RTMP/RTMPS (Publish)<br>HLS<br>SRT   |
| Network Interface             | 1x RJ45 (10/100Mbps Ethernet)   |
| <b>Recording</b>              |   |
| Recording Storage Medium      | SD Card (Class 10 above)  |
| Recording Storage File System | NTFS, FAT, exFAT  |
| Recorded File Format          | MP4   |
| Built-in Audio Mixer          | Yes, 4 channels   |
| <b>Audio</b>                  |   |
| Audio Input                   | 2x XLR(Mic)<br>2x RCA   |

|                       |  |
|-----------------------|--|
| Audio Output          | 2x Unbalanced RCA  |
| Audio Sampling        | ---  |
| Reference Input       | ---  |
| <b>Others</b>         |  |
| Control Interface     | ---  |
| Preview Display       | 14" Capacitive Touch LCD                                   |
| Controller            | ---  |
| Dimension (LxWxH)     | 438 x 331 x 114 mm   |
| Weight                | 4.3 kg   |
| Power Supply          | DC 12V, 52W  |
| Operating Temp. Range | 0~40 °C  |
| What's in the box     | 1 x KMU-300 Main Unit<br>1 x AD Switch DC 12V with AC Cord |