

產品套組

洋銘易直播GO KMU-100 Studio

GO KMU-100 Studio

视频系统	UHD & HD
视频格式	3840x2160p 23.98/24/25/29.97/30/50/59.94/60. 1080p 23.98/24/25/29.97/30 1080i 50/59.94/60 1080PsF 23.98/24/25/29.97/30 720p 50/59.94/60
视频处理	SDI: 4:2:2 HDMI: 4:2:0/4:2:2
视频输入	2 sets of SDI Input: each set of 4x SDI 1x 3Gb/s or 12Gb/s SD/HD/4K. Supports single link 4:2:2 3x 3Gb/s SD/HD/4K. Supports single link, dual link, and quad link 4:2:2 2x HDMI Input: each of HDMI support for Ultra HD 4K 60p in 4:2:0/4:2:2 2x 12G/6G/3G-SDI support 4K60 4:2:2 single link and quad link 2x HDMI 1.4b/2.0 support 4K60 4:2:0 / 4:2:2
视频输出	8x 3G/HD/SD-SDI support single link 4:2:2 2x HDMI 1.4 support 1080p/50/60 4:2:2
音频输入	SDI: 16 Ch embedded in HD/4K. 8 Ch embedded in SD HDMI: 8 Ch embedded in SD, HD and Ultra HD 4K
音频输出	SDI: 16 Ch embedded in HD/4K. 8 Ch embedded in SD. HDMI: 8 Ch embedded in SD, HD and Ultra HD 4K
支持音频轨数	SDI: 16 Ch embedded in HD/4K. 8 Ch embedded in SD. HDMI: 8 Ch embedded in SD, HD and Ultra HD 4K
视频抠像	----
USK	----
DSK	----
子母画面	----
LOGO显示	----
图片显示	----
特效	----
Tally输出	----
调音台	----
显示器	Dual 10.1" LCD
特别功能	Seamless Cut

Streaming

直播编码方式	H.264/AVC, Main/High Profile
--------	------------------------------

直播视频码流	Record Only: Up to 16Mbps (1080p50/60) Stream Only: Up to 10Mbps (1080p50/60) Rec+Stream: 10Mbps (1080p25/30)
直播音频模式	Stereo/Mono
直播音频码流	Stereo: 64~384Kbps Mono: 32~192Kbps
串流协议	TS over TCP/UDP (unicast & multicase) RTSP over HTTP/TCP/UDP (RTSP Elementary Streaming) RTMP/RTMPS (Publish) HLS
网络介面	1x RJ45 (10/100Mbps Ethernet)
直播录像格式	H.264
直播存储方式	SD Card

Recording

录像储存方式	SD Card
录像存储带宽	Removable Hard Drive, transfer data via USB 2.0
录像储存格式	NTFS, FAT, exFAT
录像储存文件格式	MP4

Audio

音频输入接口	3x XLR(2 for Line-in, 1 for Mic-in), 2x RCA
音频输出接口	2x XLR, 2x Unbalanced RCA
音频显示界面	SMT LCD
音频延迟	Up to 700ms

Others

尺寸	493 x 253 x 331 (monitor's up) 493 x 253 x 190 (monitor's down)
重量	14 kg
电源	DC 12V, 60W
操作温度	0~40 °C
附件	1 x GO KMU-100 Studio Product 1 x RMC-185 Product 1 x AD Switch DC 12V 2 x HDMI Cable 3 x BNC Cable 2 x RCA Cable 1 x Ethernet Cable 1 x RS-422 D Sub 9Pin to RJ-45 Adapter Cable 12 x Cable Ties