

手提式導播室

HD/SD 4通道HDBaseT手提式移動錄播導播室**HS-1600T MARK II**

| | |
|--------|---|
| 影像系統 | HD & SD |
| 影像格式 | 1080p 50/59.94/60Hz 1080i 50/59.94/60Hz 720p 50/59.94/60Hz 576i/p 50Hz 480i/p 59.94Hz |
| 輸入格式設定 | ---- |
| 影像輸入 | 3 x HDBaseT 1 x HDMI |
| 電腦輸入 | 1 via HDMI |
| 下變換轉換器 | Yes |
| 影像輸出 | 3x HDMI PGM 1x HDBaseT PGM 1x STREAM (RJ-45) |
| 聲音輸入 | 2x Balanced XLR 1x Stereo RCA (L/R) De-embedded Digital Audio |
| 聲音輸出 | 1x Stereo headphone |
| 聲音嵌入 | Input 2 channels, Output 2 channels |
| 聲音延遲 | ---- |
| 聲音同步切換 | ---- |
| USK | 1x USK support Lumakey |
| DSK | ---- |
| 子母畫面 | 1 |
| LOGO | ---- |
| 字幕機 | ---- |
| 混音機 | Yes, 4 channels |
| 監看螢幕 | 17.3" HD TFT LED backlit, 1920x1080 pix |
| 通話系統 | ---- |

Streaming

| | |
|--------|---|
| 串流影片編碼 | H.264 / AVC, Main/ High Profile Configurable Bit-rate up to 10Mbps |
| 串流聲音編碼 | AAC-LC Configurable bit rate range from 32Kbps to 384Kbps Sample rate: 48KHz, 16bit |

| | |
|--------|---|
| 串流協議 | TS over TCP/UDP (unicast & multicast) RTSP over HTTP/TCP/UDP (RTSP Elementary Streaming) RTMP/RTMPS (Publish) HLS SRT |
| 串流控制 | Web browser UI for configuration and control Socket commands |
| 錄製檔案系統 | FAT, exFAT, NTFS |
| 錄製檔案格式 | MP4 |
| 錄製設定控制 | Web UI for system configuration and control |

Others

| | |
|------|---|
| 特別功能 | Built-in camera controller |
| 尺寸 | 455 x 355 x 134 mm |
| 重量 | 17.2 Lbs (7.8 kg), Reinforce Plastic Case |
| 电源 | DC 48V, 4.16A |
| 操作溫度 | 0~40 °C |
| 附件 | 1 x HS-1600T MARK II Product 1 x AD Switch DC 56V with AC Cord 3 x Ethernet Cable |