

導播機

SE-1200MU 6 Input Switcher + RMC-260 Controller

Bundle

SEB-1200

影像系統	HD
影像格式	1080i 50/59.94/60Hz 720p 50/59.94/60Hz
影像處理	SDI: 4:2:2 HDMI: YUV 4:2:2 10 bit, RGB 4:4:4
輸入設定	All 6, repeatable
影像輸入	4x HD-SDI 2x HDMI (RGB/YUV, 1080i/1080p/720p)
相容HD/SD	----
電腦連結	2 via HDMI
影像輸出	2x HD-SDI 2x HDMI assignable: PGM(w/DSK 1&2), PGM(w/DSK 1), PGM Clean, PVW(w/o DSK), multi-view, Input 1-6
下轉輸出	----
多分割監看	HDMI & SDI assignable, Ethernet (MJPEG)
聲音輸入	2x Balanced XLR
聲音輸出	----
支持聲音軌數	Input 2 channels, Output 2 channels
聲音延遲	----
影音像同步切換	Yes
影像去背	2
字幕機	----
USK	2x Keyer support Chromakey/ Linear/ Luma Key
DSK	2x DSK support Lumakey/ Linear key (Key / Fill)
子母畫面	1
LOGO顯示	----
靜態圖片儲存	500
特效	FTB, Cut, 32 Wipe with border
過場預覽	Full transitions preview
同步訊號輸入/出	Built-in Genlock (internal)
Tally輸出	1x D-sub 15pin, dual color
電腦控制	Ethernet (free Window software) RS-422/ RS-232
混音器	----

特別功能	Motion JPEG Multi-view streaming (120 memory preset, BGD Transition on/off option) Free Virtual Set and Stinger transition included
外型	1RU rack-mount mainframe
尺寸	440 x 215 x 49 mm (SE-1200MU) 430 x 261 x 70 mm (RMC-260)
重量	1.5 kg (SE-1200MU) 1.3 kg (RMC-260)
電源	DC 12V, 19W (SE-1200MU) DC 12V, 0.5A (RMC-260)
操作溫度	0~40 °C
附件	SE-1200MU: 1 x SE-1200MU product 1 x AD Switch DC 12V 1 x DB9P TO DB9P Cable 2 x 1U Rack Mount Ear 6 x M4 Screws for Rack Mount Ear RMC-260: 1 x RMC-260 product 1 x AD Switch DC 12V 1 x DB9P TO DB9P Cable