

Cameras

## HDBaseT PTZ Camera for HS-1500T and HS-1600T PTC-140T

|                                  |  |
|----------------------------------|--|
| Video format/Resolution          | 1080p 60/59.94/50/30/29.97/25<br>1080i 60/59.94/50<br>720p 60/59.94/50 |
| Image Sensor                     | 1/2.8 inch high quality HD CMOS sensor                                 |
| Effective Pixels (approx.)       | 2.07 Mega pixels   |
| S/N Ratio                        | >55dB  |
| Min. Illumination                | 0.5Lux (F1.8, AGC ON)  |
| Electronic Shutter               | Auto / Manual  |
| Zoom Ratio                       | 20x Optical Zoom, 10x Digital Zoom                                     |
| Gamma Control                    | Off / Normal   |
| Iris Control                     | Auto / Manual  |
| Digital Noise Reductions         | Yes  |
| On-Screen Display (OSD)          | English/Simplified Chinese/Traditional Chinese                         |
| White Balance                    | Auto, Manual, One Push, 3000K, 4000K, 5000K, 6500K                     |
| AGC / Gain Control               | Auto / Manual  |
| HDR/WDR                          | ---  |
| Mirror / Flip Image              | Yes  |
| Focus Mode                       | Auto / Manual  |
| Panning / Tilting Range          | Pan: 340° , Tilt: +90° to -30°   |
| Panning / Tilting Speed          | Pan: 0.1~60°/sec<br>Tilt: 0.1~30°/sec                                  |
| Preset                           | 255 Position   |
| Focal Length                     | f=5.2 (wide) to 98 (tele) mm<br>F1.6 to F3.5                           |
| Field of View (Horizontal, Wide) | Approx. 54.7° (WIDE END) / 3.3° (TELE END)                             |
| Image Compensation               | Backlight Compensation   |
| Video Output                     | HDBaseT (PoE) x1<br>RJ-45 x1   |
| Audio Input                      | 3.5mm Line in  |
| Tally LED                        | Dual color (Red, Green)  |
| Lens Filter                      | M52.0 x 0.75 Thread with UV Protection                                 |
| Control Protocol                 | Pelco-D, Pelco-P,<br>VISCA, VISCA over IP, DVIP, ONVIF                 |

|                                    |   |
|------------------------------------|---|
| Remote Control Interface           | IR<br>Web GUI<br>RS-422<br>DVIP<br>HDBaseT(RJ-45)/Serial control on Receiver Box: Transmit up to 100m   |
| Video Compression Format           | H.264/H.265   |
| Audio Compression Format           | AAC, G711   |
| Audio Bitrate                      | 96Kbps, 128Kbps, 256Kbps  |
| HD IP Interface                    | 100M IP port(100BASE-TX); Support DVIP  |
| Streaming Protocols                | RTSP, RTMP(S), ONVIF, Multicast, SRT  |
| First Stream Supported Resolution  | ----  |
| Second Stream Supported Resolution | ----  |
| Video Bitrate                      | ----  |
| Video Bitrate Mode                 | ----  |
| Encoding Frame rate                | ----  |
| POE                                | ----  |
| F/W Update                         | Via Web GUI   |
| IR Control                         | Yes   |
| Camera Control Unit                | HS-1650T/HS-1600T Mark II/RMC-2P/RMC-180 series/RMC-300 series/PTZ View Assist APP  |
| Tripod Mount                       | 1/4-20 UNC  |
| Optional Accessories               | WM-1/ WM-10/ WM-11  |
| Color                              | Dark Blue/White   |
| Dimension (LxWxH)                  | 156(W) x 184(H) x 186(D)  |
| Weight                             | 1.6 kg  |
| Operating Temp. Range              | 0~40 °C   |
| Power                              | DC 12V 12W  |
| What's in the Box                  | 1 x PTC-140T Unit<br>1 x IR remote controller<br>1 x Ceiling mount bracket-A<br>1 x Ceiling mount bracket-B<br>6 x Ceiling mount bracket screw M3*4mm<br>1 x DC 12V Power Adaptor<br>1 x Power Cord<br>1 x Safety Cable<br>1 x RS-232 DB9 9 Pin to 8 Pin Mini DIN Cable |