

비디오 스위처

6 Input HD Broadcast Quality Switcher

SE-2200

Video Standard	HD & SD
Video Format	1080i 50/59.94/60Hz 720p 50/59.94/60Hz 576i 50Hz 480i 59.94Hz
Video Processing	SDI: 4:2:2 HDMI: YUV 4:2:2 10 bit, RGB 4:4:4
Input Routable / Crosspoint	All 6, repeatable
Video Input	6x HD-SDI, 2x HDMI (on CH5 & 6)
Mix HD & SD Source	----
Computer Graphic Interface	2 via HDMI
Video Output	6x SDI Outputs assignable: AUX 1-4, PGM, PVW, PGM Clean & multi-view 2x HDMI assignable: PGM or multi-view
Down-Converted Output	----
Built-in Multi-view Monitoring Out	2x HDMI
Analogue Audio Input	4x Balanced XLR
Analogue Audio Output	2x Balanced XLR
Digital Embedded Audio Support	Input up to 16 channels, Output 4 channels
Audio Delay Calibration	----
A+V Switching	Yes
Chroma key	----
Title Creator	Yes, CG-200 software free download
USK	----
DSK	2x DSK support Lumakey/ Linear key (Key / Fill)
Picture in Picture	2
Logo Insertion	2 (or 1 logo + 1 clock)
Still Store	6
Effects	FTB, Cut, 8 Wipe with border
Transition Preview	PiP & DSK
Sync / Reference In/Out	Built-in Genlock (internal)
Tally Output	1x D-sub 25pin, dual color
PC Remote Control	Ethernet (free Window software) RS-422/ RS-232

Built-in Audio Mixer	----
Special Features	6x 6 Matrix seamless switch Built in TC-200 CG interface
Chassis	2 units, 2RU rack-mount mainframe
Dimension (LxWxH)	433 x 312 x 76 mm (switcher) 432 x 252 x 88 mm (main unit)
Weight	6.1 kg
Power	DC 12V, 32W
Operating Temp. Range	0~40 °C
What's in the Box	1 x SE-2200 Main Unit 1 x SE-2200 Key Board 1 x AD Switch DC 12V with AC Cord 1 x DB9P TO DB9P Cable 1 x CB-41 / XLR to XLR Cable 12 x Screw 2 x 2U Ear Rack