

Estudio móvil

# Estudio móvil HD/SD de 8/12 entradas

## HS-2800

|                                |                                                                                            |
|--------------------------------|--------------------------------------------------------------------------------------------|
| Video Standard                 | HD & SD                                                                                    |
| Video Format                   | 1080i 50/59.94/60Hz<br>576i 50Hz<br>480i 59.94Hz                                           |
| Input Rutable / Crosspoint     | Fixed                                                                                      |
| Video Input                    | Standard:<br>8x SDI, 2x HDMI<br>Max:<br>12x SDI, 3x HDMI                                   |
| Computer Graphic Interface     | Max 3 via HDMI                                                                             |
| Down-converted Output          | 2x SDI                                                                                     |
| Video Output                   | 2x SDI assignable:<br>PGM, PVW, AUX & Clean Out<br>1x HDMI assignable:<br>PGM & multi-view |
| Analogue Audio Input           | 4x Balanced XLR                                                                            |
| Analogue Audio Output          | 2x Balanced XLR                                                                            |
| Digital Embedded Audio Support | Input up to 16 channels,<br>Output 4 channels                                              |
| Audio Delay Calibration        | Up to 8 frames                                                                             |
| A+V Switching                  | Yes                                                                                        |
| USK                            | ----                                                                                       |
| DSK                            | 2x DSK support Lumakey & Linear key<br>(Key / Fill)                                        |
| Picture in Picture             | 2                                                                                          |
| Logo Insertion                 | 2 (or 1 logo + 1 clock)                                                                    |
| Built-in Audio Mixer           | ----                                                                                       |
| Built-in Intercom & Tally      | 8 channels (4 belt-packs incl.)                                                            |

## Streaming

|                                       |      |
|---------------------------------------|------|
| Streaming                             | ---- |
| Streaming Audio Encode                | ---- |
| Streaming Protocol                    | ---- |
| Streaming Control                     | ---- |
| Recording File System                 | ---- |
| Recording File Format                 | ---- |
| Streaming & Recording Setting Control | ---- |

Others

|                       |                                                                                                                                                                                                                   |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Special Features      | ----                                                                                                                                                                                                              |
| Dimension (LxWxH)     | 455 x 355 x 134 mm                                                                                                                                                                                                |
| Weight                | 18.7 Lbs (8.5 kg), Reinforce Plastic Case                                                                                                                                                                         |
| Power                 | DC 12V, 6A                                                                                                                                                                                                        |
| Operating Temp. Range | 0~40 °C                                                                                                                                                                                                           |
| What's in the Box     | 1 x HS-2800 Unit<br>1 x AD Switch DC 12V with AC Cord<br>1 x CB-41 / XLR to XLR Cable<br>4 x CB-3 / XLR cable<br>1 x Goose neck MIC<br>4 x Headphone Microphone<br>4 x ITC-100SL<br>1 x Tally light<br>4 x Velcro |