

Sistemas de intercom

Digital Intercom System

ITC-300

| | |
|------------------------|---|
| Tally | 2 x 15 Pin D-Sub Female Sockets for Tally A and Tally B |
| MIC / Headset | 1 x 3.5mm Stereo Jack Socket (For Headphone / Microphone combination) Headset Impedance 24 ohm 100mW(min) Microphone Level -45.2dB (Tip: Mic□Ring: Phone□Sleeve: GND) |
| Headphone | 1 x 1/4" (6.3mm) Stereo Headphone Socket (Tip: Phone□Ring: Phone□Sleeve: GND) |
| Light Socket (DC 12 V) | Light Power Consumption: +5 V / 500 mA |
| Microphone | 3 Pin XLR / 1/4" (6.3mm) Socket x 1 Switchable Condenser / Dynamic Input Microphone Level -67dB PIN1:N/A,PIN2:MIC,PIN3:GND |
| Frequency Response | 300 Hz-7 KHz, < +/-3dB |
| THD | < 0.1% @1KHz |
| S/N | >70dB |
| Built-in Speaker | 3W Speaker is mute when headphones or mic / headset are connected to the ITC-300 |
| Operating Range | Up to 100m between Base Station and Slave |
| Operating Temp. Range | 0~40 °C |
| Dimension (LxWxH) | 440 x 126 x 44mm |
| Weight | 1.9 kg |
| Power | DC 12V, 3A |
| What's in the Box | 1 x ITC-300 Base Unit 4 x ITC-300SL Belt Pack 4 x Ethernet Cable 4 x Earphone Cable 4 x Headset with microphone 1 x Gooseneck Microphone 4 x Tally LED Indicator 4 x Velcro 1 x Adaptor + AC Cord |