

Decodificador de video

IP Video Decoder

NVD-35 MARK II

Audio/Video Input	<p>Stream Input</p> <ul style="list-style-type: none"> · RTSP over UDP (Unicast / Multicast) · RTSP over TCP · RTSP over HTTP · SRT (Secure Reliable Transport) caller · MPEG-TS over UDP · RTMP Pull · RTMP Push (Internal Server) · UDP raw (Unicast/Multicast) · HLS over HTTP · MPEG-TS over TCP Pull · Video sharing websites
Audio Output	<p>2 x RCA(L/R) SDI embedded audio</p>
Video Output	<p>Composite (analogue) SDI (digital)</p>
Network Feature	<p>1x RJ-45 Female (10/100M Ethernet) DHCP/Static IP</p>
Supported Video Resolution	<p>1080p 60/59.94/30/29.97/25/24 1080i 60/59.94/50 720p 60/59.94/50 576i 50 (PAL) 480i 60 (NTSC)</p>
Supported Decoding Resolution	<p>Up to 1080p60/50</p>
Control	<p>Web browser UI for configuration and control. TCP/IP Socket commands</p>
Update	<p>Automatic firmware upgrade</p>
Power	<p>Input AC 100~240V Switching Adaptor Output DC 12V / 1A</p>
Environmental Conditions	<p>Operating temperature: 0~40°C, Storage temperature: -10~60°C</p>
Dimension (LxWxH)	<p>220 x 143 x 47 mm</p>
Weight	<p>1 kg</p>
Power	<p>DC 12V, 1A</p>
What's in the Box	<p>1 x NVD-35 MARK II product 1 x AD Switch DC 12V 1 x Remote Control</p>