

Mobile Cast

# HD 6-Channel Portable Mobile Cast Video Studio

## HS-2200

|                                |                                                                                                                     |
|--------------------------------|---------------------------------------------------------------------------------------------------------------------|
| Video Standard                 | HD & SD                                                                                                             |
| Video Format                   | 1080i 50/59.94/60Hz<br>720p 50/59.94/60Hz<br>576i 50Hz<br>480i 59.94Hz                                              |
| Input Routable / Crosspoint    | All 6, repeatable                                                                                                   |
| Video Input                    | 6x HD-SDI, 2x HDMI<br>(on CH5 & 6)                                                                                  |
| Computer Graphic Interface     | 2 via HDMI                                                                                                          |
| Down-converted Output          | ----                                                                                                                |
| Video Output                   | 5x SDI Outputs assignable:<br>AUX 1-4, PGM, PVW, PGM Clean or multiview<br>1x HDMI assignable:<br>PGM or multi-view |
| Analogue Audio Input           | 4x Balanced XLR                                                                                                     |
| Analogue Audio Output          | 2x Balanced XLR                                                                                                     |
| Digital Embedded Audio Support | Input up to 16 channels,<br>Output 4 channels                                                                       |
| Audio Delay Calibration        | ----                                                                                                                |
| A+V Switching                  | Yes                                                                                                                 |
| USK                            | ----                                                                                                                |
| DSK                            | 1, support Luma-key & Linear key (Key / Fill)                                                                       |
| Picture in Picture             | 2                                                                                                                   |
| Logo Insertion                 | 2 (or 1 logo + 1 clock)                                                                                             |
| Title Creator                  | Yes, CG-200 software free download                                                                                  |
| Built-in Audio Mixer           | ----                                                                                                                |
| Built-in Intercom & Tally      | 8 channels (4 belt-packs incl.)                                                                                     |

## Streaming

|                                       |      |
|---------------------------------------|------|
| Streaming                             | ---- |
| Streaming Audio Encode                | ---- |
| Streaming Protocol                    | ---- |
| Streaming Control                     | ---- |
| Recording File System                 | ---- |
| Recording File Format                 | ---- |
| Streaming & Recording Setting Control | ---- |

Others

|                       |                                                                                                                                                                                                                   |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Special Features      | Built in TC-200 CG interface<br>6x6 matrix seamless switch                                                                                                                                                        |
| Dimension (LxWxH)     | 455 x 355 x 134 mm                                                                                                                                                                                                |
| Weight                | 16.5 Lbs (7.5 kg), Reinforce Plastic Case                                                                                                                                                                         |
| Power                 | DC 12V, 5A                                                                                                                                                                                                        |
| Operating Temp. Range | 0~40 °C                                                                                                                                                                                                           |
| What's in the Box     | 1 x HS-2200 Unit<br>1 x AD Switch DC 12V with AC Cord<br>1 x CB-41 / XLR to XLR Cable<br>4 x CB-3 / XLR cable<br>1 x Goose neck MIC<br>4 x Headphone Microphone<br>4 x ITC-100SL<br>1 x Tally light<br>4 x Velcro |