LCD Monitors

# 7" 4K LCD Monitor

**TLM-700K**

| | |
|---|---|
| Screen | 7" TFT LCD |
| Chassis | Camera Mount |
| Resolution | 1920x1200 |
| Viewing Angle | (H) +85/-85°<br>(V) +85/-85° |
| Luminance/Contrast | 450cd/m²<br>1000:1 |
| Video Inputs | 1x HDMI (1.4b),<br>HDCP 1.4 |
| Loop Through | 1x HDMI (1.4b) |
| Supported Input Resolutions | 4096x2160p(24Hz),<br>3840x2160p(23/24/25/29/30Hz),<br>2048x1080p(50/59.94/60Hz),<br>1080p(23.98/24/25/29.97/30/50/59.94/60Hz),<br>1080i(50/59.94/60Hz),<br>720p(23.98/24/25/29.97/30/50/59.94/60Hz),<br>576i(50Hz), 576p(50Hz),<br>480i(59.94/60Hz), 480p(59.94/60Hz) |
| Aspect Ratio | Full/16:9/1.85:1/2.35:1/4:3/3:2 |
| Aspect Marker | Off/16:9/1.85:1/2.35:1/4:3/3:2/9:16 |
| Safty Marker | Off/95%/93%/90%/88%/85%/80% |
| Tally LED | ---- |
| Audio In/Out | Embedded Audio (48KHz sampling)<br>Analog Stereo (Phone Jack),<br>Speaker x1 (2W) |
| Special Features | Focus assist (peaking), False Color, Histogram,<br>Exposure, Pixel to Pixel Zoom, Underscan, Check Field (blue-only mode, monochrome mode) |
| Dimension (WxHxD) | 182 x 129 x 37 mm |
| Weight | 0.3 kg |
| Operating Temp. Range | 0~40 °C |
| Power | DC 12V, 12W |
| What's in the Box | 1 x TLM-700K product<br>1 x AD Switch DC 12V<br>1 x Folding sun shade cover<br>1 x HDMI A/C cable<br>1 x Battery plate<br>1 x Hot shoe mount |