

Видеомикшеры

4-входовой HD видеомикшер SE-500MU

Video Standard	Full HD & SD
Video Format	1080p 50/59.94/60Hz 1080i 50/59.94/60Hz 720p 50/59.94/60Hz 576i 50Hz 480i 59.94Hz
Video Processing	HDMI: YUV 4:4:4 10 bit, RGB: 4:4:4
Input Routable / Crosspoint	----
Video Input	4x HDMI
Mix HD & SD Source	Yes
Computer Graphic Interface	4 via HDMI
Video Output	2 x HDMI (1 is MV, 1 is PGM)
Down-Converted Output	Yes
Built-in Multi-view Monitoring Out	HDMI
Analogue Audio Input	1 x Stereo RCA (L/R) 2 x Mono Microphone De-embedded Digital Audio (2 CH)
Analogue Audio Output	1 x Stereo RCA (L/R) Embedded Digital Audio (2 CH)
Digital Embedded Audio Support	Embedded 2-CH digital/analogue audio
Audio Delay Calibration	----
A+V Switching	Yes
Chromakey	----
Title Creator	----
USK	Lumakey
DSK	----
Picture in Picture	1
Logo Insertion	----
Still Store	----
Effects	FTB, Cut, Wipe with border
Transition Preview	----
Sync / Reference In/Out	Built-in Genlock (internal)
Tally Output	1x D-sub 15pin, dual color
PC Remote Control	Via Ethernet (free Window software) or RS-232
Camera Control	----

Built-in Audio Mixer	----
Storage	----
Recording File System	----
Recording File Format	----
Video Encode	----
Audio Encode	----
Streaming Protocol	----
Firmware Update	USB
Special Features	Support Apple iOS, Apple Mac, Android Control Built-in video scaler for mixed resolution inputs
Chassis	1 RU Rackmount
Dimension (LxWxH)	440 x 215 x 49 mm
Weight	2.4 kg
Power	DC 12V, 20W
Operating Temp. Range	0~40 °C
What's in the Box	1 x SE-500MU product 1 x AD Switch DC 12V 2 x L-Type Fixed Film