

Virtual Studio

# 3D Tracking VR/AR 4K Virtual Studio System

## TVS-3000

| Tracking/Trackless        | Tracking & Trackless  |
|---------------------------|---|
| Video Input               | 4K mode:<br>6G-SDI x 2 or 12G-SDI x 1<br>HD mode:<br>3G-SDI x 3   |
| Video Output              | 4K mode:<br>HDMI 2.0 x 1<br>HD mode:<br>3G-SDI x 1 + HDMI x 1   |
| Video Input/Output Format | SDI Input/Output:<br>2160p 60/50/30/25 (Input only)<br>1080p 30/25<br>1080i 60/50<br>720p 60/50/30/25<br>HDMI Output:<br>2160p 60/50/30/25<br>1080p 60/50/30/25<br>720p 60/50/30/25 |
| Audio Input               | Mini Phone Jack x 1<br>SDI audio embedded   |
| Operation Monitor         | DP x2   |
| Tally                     | Coming Soon   |
| Media                     | 3(DDR)  |
| Virtual Studio            | 10 & Unlimited download from <a href="http://datavideovirtualset.com">datavideovirtualset.com</a>   |
| Still Picture             | 1   |
| Still Text                | 2   |
| Keyer                     | Chromakey upto 8CH  |
| Recording                 | Lossless 4:2:2 (.avi)<br>H.265 (.mov)<br>H.264 (.mp4;.wmv)<br>MPEG-2 (.ts;.mxf)   |
| Live Streaming Protocols  | TS over UDP<br>TS over TCP<br>RTMP<br>RTMPS<br>RTSP   |
| Hard Disk Capacity        | 4TB HDD + 500G SSD  |
| Dimension (LxWxH)         | 480 x 470 x 178mm   |
| Weight                    | 13.6 kg   |
| Operating Temp. Range     | 0~40 °C   |
| Power                     | AC 100-240V 750W  |

|                   |  |
|-------------------|--|
| What's in the Box | 1 x TVS-3000A Main Unit<br>1 x Power AC Cord<br>1 x USB Mouse<br>1 x RMC-285 Unit(Include D-Sub 9 PIN Cable + DC 12V power adaptor)<br>1 x 802.11AC Antenna / or USB dongle<br>1 x LBK-2 |
|-------------------|--|