

Datavideo Product Compare

<https://www.datavideo.com/sg/>

| | |
|------------------------|--|
| Model Number | ITC-100 |
| Product | Intercom System |
| Tally | 2 x 15 Pin DSub Sockets for Tally A and B |
| MIC / Headset | 3.5 mm Stereo Jack Socket for Headphone / Microphone combination Headset Impedance 8-600 Ohms 100 mW (min) |
| Headphone | ¼" (6.3mm) Stereo Headphone Socket Headset Impedance 8-600 Ohms 100 mW (min) |
| Light Socket (DC 12 V) | 3 PIN XLR Connector PIN 2: 12V PIN 3: GND Light Power Consumption: 12 V / 100 mA (MAX.) |
| Microphone | 3 PIN XLR / ¼" (6.3mm) Jack Microphone Socket Switchable Condenser / Dynamic Input Microphone Level -67 dB |
| Frequency Response | 550-3.6 kHz, <+/- 3dB |
| THD | < 3% |
| S/N | > 50dB |
| Built-in Speaker | 70mm x 30mm 32 Ohm 3 Watts |
| Operating Range | Up to 200 meters between base station and slave |
| Operating Temp. Range | 0~40 °C |

| | |
|-------------------|--|
| Dimension (LxWxH) | 482 x 127 x 46 mm |
| Weight | 1.9 kg |
| Power | DC 12V, 8W |
| What's in the Box | <ul style="list-style-type: none"> 1 x ITC-100 Base Unit 4 x ITC-100SL Belt Pack 4 x ITC-100SL Carry Case 4 x Cable 5pin XLR to XLR 4 x 3.5mm Jack to 3.5mm Jack Cable 4 x Headset with microphone 4 x Tally LED Indicator 1 x XLR Gooseneck Microphone 1 x XLR Gooseneck Light 1 x 12V 1A Power Supply Unit |