

Datavideo Product Compare

<https://www.datavideo.com/tw/>

型號	PTC-200T
產品	4K 雲台攝影機 (HDBaseT)
影像格式	2160p 29.97/25 1080p 59.94/50 1080i 59.94/50 720p 59.94/50
感光元件	1/2.3" type Exmor R CMOS
有效畫素	8.93 Mega pixels
信噪比	---
最小明亮度	50%, High Sensitivity Mode: Color: 0.75 lx (F1.8, AGC on, 1/30 sec) 50%, Normal Mode: Color: 3 lx (F1.8, AGC on, 1/30 sec)
電子快門	1/25 (1/30), 1/50 (1/60), 1/75(1/90), 1/100, 1/120 (1/125), 1/150(1/180), 1/215(1/250), 1/300(1/350), 1/425(1/500), 1/600(1/725), 1/1000, 1/1250(1/1500) sec
鏡頭倍率	12x Optical Zoom
有效變焦倍率	
Gamma	Off / Normal / Standard Mode 1-4
光圈設定	Auto / Manual
數位降噪	Yes
選單使用語言	English
白平衡	Auto, Indoor, Outdoor, Sodium Vapor Lamp, One-push, Manual

ACG/增益控制	Auto/Manual (0 dB to 33 dB) Max. Gain Limit (9 dB to 33 dB)
HDR/WDR	
鏡頭翻轉	Yes
對焦模式	Auto (Sensitivity: normal, low), One-push AF, Manual, Zoom Trigger AF
水平/垂直範圍	Pan: 270° , Tilt: +90° to -17°
水平/垂直移動速度	Manual: 1~150°/Sec Swing: 1~150°/Sec
預設點	50 Position
焦距	f = 3.9 mm (wide) to 46.8 mm (tele)
視角	Approx. 70.7° (WIDE END) / 6.4° (TELE END)
圖像補償	Day & Night Function
影像輸出	HDMI x1 3G-SDI x1 HDBaseT x 1 to PTC-200T Receiver Box
聲音輸入	----
Tally燈	Dual color (Red, Green)
濾片或廣角鏡	N/A
Protocol	VISCA, DVIP
遠端控制端子	RS-422: Transmit up to 1000m HDBaseT (RJ-45)/ DVIP on Receiver Box: Transmit up to 70m (4K image)
影像壓縮格式	----
聲音壓縮格式	----
聲音比特率	----
HD IP Interface	----
串流協議	----

第一串流直 播解析度	----
第二串流直 播解析度	----
影像比特率	----
影像比特率 模式	----
編碼 Frame rate	----
POE	----
韌體更新	USB
IR控制	Yes
攝影機控制 器	HS-1500T/HS-1600T series/RMC-180 series/RMC-300 series
腳架用螺絲 尺寸	1/4-20 UNC
可用附件	WM-1/ WM-10/ WM-11
顏色	Dark blue
尺寸	173 x 189 x 219 mm
重量	2.8 kg
操作溫度	0~40 °C
電源	DC 12V 33W
附件	1 x PTC-200T product 1 x HBT-11 Receiver Box 1 x IR remote controller 1 x Ceiling mount bracket-A 1 x Ceiling mount bracket -B 6 x Ceiling mount bracket screw M3*4mm 1 x DC 12V Power Adaptor 1 x DC 48V Power Adaptor 2 x Power Cord 1 x A tightrope 1 x Phoenix connector to RJ-45

