

# Datavideo Product Compare

<https://www.datavideo.com/us/>

|                               |  |
|-------------------------------|--|
| Model Number                  | <b>NVD-30 MARK II</b>  |
| Product                       | <b>HDMI IP Video Decoder</b>   |
| Audio/Video Input             | Stream Input <ul style="list-style-type: none"><li>· RTSP over UDP (Unicast / Multicast)</li><li>· RTSP over TCP</li><li>· RTSP over HTTP</li><li>· SRT (Secure Reliable Transport) caller</li><li>· MPEG-TS over UDP</li><li>· RTMP Pull</li><li>· RTMP Push (Internal Server)</li><li>· UDP raw (Unicast/Multicast)</li><li>· HLS over HTTP</li><li>· MPEG-TS over TCP Pull</li><li>· Video sharing websites</li></ul> |
| Audio Output                  | 2 x RCA(L/R)<br>HDMI embedded audio  |
| Video Output                  | Composite (analogue)<br>HDMI (digital)   |
| Network Feature               | 1x RJ-45 Female (10/100M Ethernet) DHCP/Static IP  |
| Supported Video Resolution    | 1080p 60/59.94/30/29.97/25/24<br>1080i 60/59.94/50<br>720p 60/59.94/50<br>576i 50 (PAL)<br>480i 60 (NTSC)  |
| Supported Decoding Resolution | Up to 1080p60/50   |

|                          |  |
|--------------------------|--|
| Control                  | Web browser UI for configuration and control.<br>TCP/IP Socket commands  |
| Update                   | Automatic firmware upgrade   |
| Power                    | Input AC 100~240V Switching Adaptor<br>Output DC 12V / 0.5 A             |
| Environmental Conditions | Operating temperature: 0~40°C, Storage temperature: -10~60°C             |
| Dimension (LxWxH)        | 220 x 143 x 47 mm  |
| Weight                   | 1 kg   |
| Power                    | DC 12V, 0.5A   |
| What's in the Box        | 1 x NVD-30 MARK II product<br>1 x AD Switch DC 12V<br>1 x Remote Control |